

**In the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Claims 1- 14 (Canceled)**

15. (Currently Amended) A method for real time virtual positioning of a sound source in three dimensional space as perceived during playback, comprising the steps of:

~~processing the~~ processing a non-binauralized input sound signal to provide a plurality of sound signals, each of the plurality of sound signals corresponding to one of a plurality virtual locations disposed in an azimuthal plane with respect to a listening position;

repositioning select ones of the plurality of virtual locations to apparent positions above and below the azimuthal plane;

mixing the plurality of sound signals including the sound signals corresponding to the repositioned select ones of the plurality of virtual locations, to provide the a binauralized output including a left output signal and the and a right output signal; and

playing the left and right output signals through respective left and right loudspeakers of a localized speaker headset.

16. (Canceled)

17. (Previously Presented) The method of Claim 15, wherein the step of processing the non-binauralized input sound signal comprises the steps of:

selecting portions of each channel of the non-binauralized input sound signal;

blending the selected portions according to a predetermined mixing plan to generate a

5 composite sound signal; and

coupling the composite signal to an external loudspeaker.

AMENDMENT AND RESPONSE  
S/N 09/392,208  
Atty. Dkt. No. OXMO-24,721

18. (Original) The method of Claim 15, wherein the step of playing comprises the steps of:  
supporting the left and right loudspeakers proximately in the plane of the zygomatic arch  
of the listener in rearward facing relationship with respect to the listener's head for radiating sound  
toward the pinna of the listener's respective left and right ears; and  
5 coupling the left and right output signals to corresponding left and right signal inputs of  
the localized speaker headset.

19. (Original) The method of Claim 18, wherein the step of supporting comprises the step  
of:  
locating the left and right loudspeakers proximate and not in contact with the respective  
left and right ears of the listener so as to avoid disturbing the conch resonance of the listener's ears.

20. (Original) The method of Claim 18, wherein the step of supporting comprises the step  
of:  
locating the left and right loudspeakers proximate and not in contact with the respective  
left and right ears of the listener such that the natural left-right and right-left separation of signals by the  
5 listener's head is maintained.

21. (Original) The method of Claim 15, comprising the step of:  
associating a video image with the non-binauralized input sound signal.

22. (Original) The method of Claim 21, wherein the step of associating a video image  
comprises the steps of:  
associating an external loudspeaker with the video image;  
positioning the external loudspeaker proximate the video image and facing in the same  
5 direction as a line of sight from the central portion of the video image to the listener; and  
reproducing a portion of the non-binauralized input sound signal in the external  
loudspeaker.

AMENDMENT AND RESPONSE  
S/N 09/392,208  
Atty. Dkt. No. OXMO-24,721

23. (Original) The method of Claim 22, wherein the step of reproducing comprises the steps of:

selecting portions of each channel of the non-binauralized input sound signal;

blending the selected portions according to a predetermined mixing plan to generate a

5 composite sound signal; and

coupling the composite sound signal to the external loudspeaker.

24. (Original) The method of Claim 22, wherein the portion of the non-binauralized input sound signal reproduced by the external loudspeaker comprises voice sounds.

25. (Original) The method of Claim 22, wherein the portion of the non-binauralized input sound signal reproduced by the external loudspeaker comprises a select portion of the audible frequency spectrum of the non-binauralized input sound signal.

26. (Original) The method of Claim 25, wherein the select portion of the audible frequency spectrum of the non-binauralized input sound signal includes low frequency tones.

27. (Original) The method of Claim 15, wherein the non-binauralized input sound signal is a monaural sound signal.

28. (Original) The method of Claim 15, wherein the non-binauralized input sound signal is a stereo sound signal.

29. (Original) The method of Claim 15, wherein the non-binauralized input sound signal is a surround sound signal.

30. (Original) The method of Claim 15, wherein the input sound signal is a binaural sound signal.

**AMENDMENT AND RESPONSE**  
S/N 09/392,208  
Atty. Dkt. No. OXMO-24,721

31. (Currently Amended) The method of Claim ~~46~~ 15, wherein the step of processing comprises the step of:

changing attributes of the signals representing the non-binauralized input sound signals, the attributes selected from the group including intensity, phase and signal delay with respect to the corresponding original non-binauralized input sound signal and/or with respect to another non-binauralized input sound signal.

32. (Currently Amended) The method of Claim ~~46~~ 15, wherein the perceived virtual locations of the sound signals do not vary with movement of the listener or of the listener's head in the azimuthal plane at the listening location.

33. (Currently Amended) A method for real time virtual positioning of a sound signal in three dimensional space as perceived during playback, comprising the steps of:

inputting a stereo audio signal from a video program prerecorded to include surround sound audio;

decoding the surround sound audio to provide a plurality of surround sound signals;

processing the plurality of surround sound signals to position each of them as virtual locations disposed in an azimuthal plane with respect to a listening position;

repositioning select ones of the plurality of surround sound signals in virtual locations to apparent positions above and below the azimuthal plane;

mixing the plurality of surround sound signals representing virtual locations including repositioned select ones of the plurality of surround sound signals in virtual locations to provide a binauralized output including a the left output signal and the right a right output signal;

playing the left and right output signals through respective left and right localized loudspeakers; and

wherein the perceived virtual locations of the sound signals do not vary with movement of the listener or of the listener's head in the azimuthal plane at the listening location.

34. (Canceled)

AMENDMENT AND RESPONSE

S/N 09/392,208

Atty. Dkt. No. OXMO-24,721

35. (Previously Presented) The method of Claim 33, wherein the step of processing said plurality of surround sound signals comprises the steps of:

selecting portions of each channel of the surround sound signal;

5 blending the selected portions according to a predetermined mixing plan to generate a composite sound signal; and

coupling the composite signal to an external loudspeaker.

36. (Original) The method of Claim 33, wherein the step of playing comprises the steps of: supporting the left and right localized loudspeakers proximately in the plane of the zygomatic arch of the listener in rearward facing relationship with respect to the listener's head for radiating sound toward the pinna of the listener's respective left and right ears; and

5 coupling the left and right output signals to corresponding left and right signal inputs of the left and right localized loudspeakers.

37. (Original) The method of Claim 36, wherein the step of supporting comprises the step of:

5 locating the left and right localized loudspeakers proximate and not in contact with the respective left and right ears of the listener so as to avoid disturbing the conch resonance of the listener's ears.

38. (Original) The method of Claim 36, wherein the step of supporting comprises the step of:

5 locating the left and right localized loudspeakers proximate and not in contact with the respective left and right ears of the listener such that the natural left-right and right-left separation of signals by the listener's head is maintained.

39. (Original) The method of Claim 33, comprising the step of:

associating the video program image with the stereo audio signal.

AMENDMENT AND RESPONSE  
S/N 09/392,208  
Atty. Dkt. No. OXMO-24,721

40. (Original) The method of Claim 39 comprising the steps of:  
associating an external loudspeaker with the video image;  
positioning the external loudspeaker proximate the video image and facing in the same  
5 direction as a line of sight from the central portion of the video image to the listener; and  
reproducing a portion of the stereo audio signal in the external loudspeaker.

41. (Original) The method of Claim 40, wherein the step of reproducing comprises the steps  
of:  
selecting portions of each channel of the stereo audio signal;  
blending the selected portions according to a predetermined mixing plan to generate a  
5 composite sound signal; and  
coupling the composite sound signal to the external loudspeaker.

42. (Original) The method of Claim 40, wherein the portion of the stereo audio signal  
reproduced by the external loudspeaker comprises voice sounds.

43. (Original) The method of Claim 40, wherein the portion of the stereo audio signal  
reproduced by the external loudspeaker comprises a select portion of the audible frequency spectrum  
of the stereo audio signal.

44. (Original) The method of Claim 43, wherein the select portion of the audible frequency  
spectrum of the stereo audio signal includes low frequency tones.

45. (Currently Amended) The method of Claim ~~34~~, 33, wherein the step of processing  
comprises the step of:  
changing attributes of the signals representing the surround sound signals, the attributes  
selected from the group including intensity, phase and signal delay with respect to the corresponding  
5 original signal and/or with respect to another input sound source signal.

**AMENDMENT AND RESPONSE**  
S/N 09/392,208  
Atty. Dkt. No. OXMO-24,721

46. (Canceled)

47. (Currently Amended) Apparatus for real time virtual positioning of a sound source in three dimensional space as perceived during playback, comprising:

means for ~~processing said processing~~ a non-binauralized input sound signal to provide a plurality of sound signals, each of the plurality of sound signals corresponding to one of a plurality  
5 of virtual locations disposed in an azimuthal plane with respect to a listening positioning;

means for repositioning select ones of said plurality of the sound signals corresponding  
to the virtual locations to apparent positions above and below said azimuthal plane;

means for mixing said plurality of sound signals including repositioned select ones of  
said plurality of virtual locations, to provide said a binauralized output including a left output signal and  
10 said right a right output signal; and

means for playing said left and right output signals through respective left and right  
loudspeakers of a localized speaker headset.

48. (Canceled)

49. (Previously Presented) The apparatus of Claim 47, wherein said means for processing  
said non-binauralized input sound signal comprises:

means for selecting portions of each channel of said non-binauralized input sound signal;

means for blending said selected portions according to a predetermined mixing plan to  
5 generate a composite sound signal; and

means for coupling said composite signal to an external loudspeaker.

AMENDMENT AND RESPONSE  
S/N 09/392,208  
Atty. Dkt. No. OXMO-24,721

50. (Original) The apparatus of Claim 47, wherein the means for playing comprises:  
means for supporting said left and right loudspeakers proximately in the plane of the  
zygomatic arch of a listener in rearward facing relationship with respect to said listener's head for  
radiating sound toward the pinna of said listener's respective left and right ears; and  
5 means for coupling said left and right output signals to corresponding left and right signal  
inputs of said localized speaker headset.

51. (Original) The apparatus of Claim 47, comprising:  
means for associating a video image with said non-binauralized input sound signal.

52. (Original) The apparatus of Claim 51, wherein said means for associating a video image  
comprises:  
an external loudspeaker for association with said video image;  
means for positioning said external loudspeaker proximate said video image and facing  
5 in the same direction as a line of sight from the central portion of said video image to said listener; and  
means for reproducing a portion of said non-binauralized input sound signal in said  
external loudspeaker.

53. (Original) The apparatus of Claim 52, wherein said means for reproducing comprises:  
means for selecting portions of each channel of said non-binauralized input sound signal;  
means for blending said selected portions according to a predetermined mixing plan to  
generate a composite sound signal; and  
5 coupling said composite sound signal to said external loudspeaker.

54. (Currently Amended) Apparatus for real time virtual positioning of a sound source in  
three dimensional space as perceived during playback, comprising:  
means for inputting a stereo audio signal from a video program prerecorded to include  
surround sound audio;

AMENDMENT AND RESPONSE  
S/N 09/392,208  
Atty. Dkt. No. OXMO-24,721



10

5 means for decoding said surround sound audio to provide a plurality of surround sound signals;

means for processing said plurality of surround sound signals to position each of them as virtual locations disposed in an azimuthal plane with respect to a listening position;

10 means for repositioning select ones of said plurality of surround sound signals in virtual locations to apparent positions above and below said azimuthal plane;

means for mixing said plurality of surround sound signals representing said virtual locations including repositioned select ones of said plurality of surround sound signals in virtual locations to provide a binauralized output including said left output signal and said right output signal; and

15 means for playing said left and right output signals through respective left and right localized loudspeakers.

55. (Canceled)

56. (Previously Presented) The apparatus of Claim 54, wherein said means for processing said plurality of surround sound signals comprises:

means for selecting portions of each channel of said surround sound signal;

5 means for blending said selected portions according to a predetermined mixing plan to generate a composite sound signal; and

means for coupling said composite signal to an external loudspeaker.

57. (Original) The apparatus of Claim 54, comprising:

means for supporting said left and right localized loudspeakers proximately in the plane of the zygomatic arch of a listener in rearward facing relationship with respect to said listener's head for radiating sound toward the pinna of said listener's respective left and right ears; and

5 means for coupling said left and right output signals to corresponding left and right signal inputs of said left and right localized loudspeakers.

AMENDMENT AND RESPONSE

S/N 09/392,208

Att. Dkt. No. OXMO-24,721

11

58. (Original) The apparatus of Claim 54, comprising:  
means for associating a video image of said video program with said stereo audio signal.

59. (Original) The apparatus of Claim 58, wherein said means for associating said video image comprises:

associating an external loudspeaker with said video image;

positioning said external loudspeaker proximate said video image and facing in the same  
5 direction as a line of sight from the central portion of said video image to a listener; and

reproducing a portion of said stereo audio signal in said external loudspeaker.

60. (Original) The apparatus of Claim 59, wherein said means for reproducing comprises:

means for selecting portions of each channel of said stereo audio signal;

means for blending said selected portions according to a predetermined mixing plan to  
generate a composite sound signal; and

5 coupling said composite sound signal to said external loudspeaker.

**AMENDMENT AND RESPONSE**

S/N 09/392,208

Atty. Dkt. No. OXMO-24,721